



JB/T2300-1999
130 serie

Number	Basic Type	Dimensions			Installation hole size				Structure size				Weight Reference (KG)	
	Toothless D _L mm	D mm	d mm	H mm	D ₁ mm	D ₂ mm	n	Φ mm	n ₁	D ₃ mm	d ₁ mm	H ₁ mm		h mm
1	130.25.500	634	366	148	598	402	24	18	4	474	463	138	32	191
2	130.25.560	694	426	148	658	462	24	18	4	534	523	138	32	214
3	130.25.630	764	496	148	728	532	28	18	4	604	593	138	32	240
4	130.25.710	844	576	148	808	612	28	18	4	684	673	138	32	272
5	130.32.800	964	636	182	920	680	36	22	4	770	759	172	40	459
6	130.32.900	1064	736	182	1020	780	36	22	4	870	859	172	40	519
7	130.32.1000	1164	836	182	1120	880	40	22	5	970	959	172	40	577
8	130.32.1120	1284	956	182	1240	1000	40	22	5	1090	1079	172	40	650
9	130.40.1250	1445	1055	220	1393	1107	45	26	5	1213	1200	210	50	1038
10	130.40.1400	1595	1205	220	1543	1257	45	26	5	1363	1350	210	50	1170
11	130.40.1600	1795	1405	220	1743	1457	48	26	6	1563	1550	210	50	1341
12	130.40.1800	1995	1605	220	1943	1657	48	26	6	1763	1750	210	50	1518
13	130.45.2000	2221	1779	231	2155	1845	60	33	6	1967	1945	219	54	1949
14	130.45.2240	2461	2019	231	2395	2085	60	33	6	2207	2185	219	54	2197
15	130.45.2500	2721	2279	231	2655	2345	72	33	8	2467	2445	219	54	2590
16	130.45.2800	3021	2579	231	2955	2645	72	33	8	2767	2745	219	54	2932
17	130.50.3150	3432	2868	270	3342	2958	72	45	8	3104	3090	258	65	4551
18	130.50.3550	3832	3268	270	3742	3358	72	45	8	3504	3490	258	65	5178
19	130.50.4000	4282	3718	270	4192	3808	80	45	8	3954	3940	258	65	5751
20	130.50.4500	4782	4218	270	4692	4308	80	45	8	4454	4440	258	65	6521